



NX-1700

The NX-1700 supports 4 Mbps of WAN bandwidth and 8,000 flows. The NX-1700's quiet operations and flexible mounting options make it ideal platform for small and remote office environments.

Capacity	
WAN Bandwidth Capacity (all features + encryption)	4 Mbps
Simultaneous Connections	8,000
Resiliency	
Disk Drives	Single
Power Supplies	Single
Network	1+1 and N+1 with VRRP or WCCP
RAM	ECC memory
MTBF	62,788 hours (7.2 years)
Security	
Disk Encryption	128-bit AES
Network Encryption	IPsec (256-bit AES)
Connectivity	
LAN/WAN Ethernet	4 x 10/100/1000 LAN/WAN (2 LAN/ 2 WAN) as per IEEE 802.3i, 802.3u, 802.3ab, 802.1Q
Management	2 x 10/100/1000; Console port
Deployment	
In-line Bridge Mode	In-line between L2 switch and WAN router with fail-to-wire in case of failure
Out-of-Path (Router) Mode	Attached to WAN router out-of-path with PBR re-direction, WCCP, and VRRP
Power	
Requirement	100-240VAC / 47-63Hz / 46W / 157 BTU or less
Power Adapter	Single

Dimensions	
Height	1.75 in (44.4 mm) or less
Width	16.9 in (430 mm) or less
Depth	10.9 in (277 mm) or less
Weight	8.8 lbs (4 kg) or less
Regulatory	
EMC	FCC Part 15 Class A, EN 55022 Class A, VCCI Class A, EN 61000-3-2/3-3, 55024
Safety	UL/cUL/60950, EN 60950
Environmental	
Temperature (Operating)	10° C to 35° C (50° F to 95° F)
Temperature (Storage)	-40° C to 65° C (-40° F to 149° F)
Humidity (Operating)	8% to 90% relative humidity, non-condensing
Humidity (Storage)	8% to 95% relative humidity, non-condensing
Altitude (Operating)	Up to 10,000 ft (3,048 m)
Altitude (Storage)	Up to 40,000 ft (12,192 m)
Management	
CLI	Full-featured CLI available over DB-9 console port or SSH
GUI	Web-based Appliance Manager available via HTTPS (default) or HTTP Global Management Systems (GMS) provides centralized configuration, monitoring, and management of multiple NX appliance
SNMP	SNMPv2c, SNMPv3
Secure Access	SSH and HTTPS
Logging	Syslog with configurable levels. Email alerts
Authentication	Local database, RADIUS, TACACS+
Statistics	Graphing and monitoring, real-time and historical

Company Address

Silver Peak Systems, Inc
2860 De La Cruz Blvd.
Santa Clara, CA 95050

Phone & Fax

Phone: +1 888 598 7325
Local: +1 408 935 1800

Online

Email: info@silver-peak.com
Website: www.silver-peak.com